

MACAULAY 4150



CHARACTERISTICS

- Steel safety hook
- Equipped with automatic locking mechanism
- Opening: 18 mm
- Maximum resistance: 25 kN

Article number: 8.84.150.00

SUITABLE FOR WORK IN, E.G.:

- Scaffolding
- Construction
- Installation technology
- Aerial platforms
- Offshore
- Petrochemicals

PACKAGING

- 1 piece (polybag)
- 10 pieces per bag
- 100 pieces (case)

CE 0598
EN 362:2004

ITEM INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 10 PIECES (BAG)	EAN CODE 100 PIECES (CASE)
One size	8.84.150.00	8718249047589	8718249061462	8718249047596

STORAGE REQUIREMENTS

During transport, keep the connector in its packaging, well away from any cutting surface. Clean it with cotton cloth or soft brush. Do not use any abrasive material/water. The metal parts should be wiped with a cloth impregnated with paraffin oil. Never use bleach or detergents. The connector should be stored in its packaging in a warm, dry, ventilated place, protected from sunlight, heat and chemicals.

TESTING INSTITUTE

This fall protection is certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonree, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link:
www.oxxa-safety.com/doc

RELATED PRODUCTS



WADDINGTON 4151

Aluminium karabiner
Article no. 8.84.151.00

YOUR SUPPLIER: