

MIKENO 4177



CHARACTERISTICS

- Automatic retractable fall arrest device with steel cable (diameter 4.5 mm) and equipped with automatic shock absorber with fall indicator
- Brake system integrated in the housing
- Suitable for vertical use (max. 140 kg)
- Includes one steel karabiner (opening 18 mm) and one steel musketon hook (opening 21 mm)
- Equipped with an NFC chip under the label designed for mapping users and keeping track of inspection schedules
- The maximum angle of inclination is 40°
- Maximum resistance: 12 kN
- Length: 10 m
- Fall factor 0

Article number: 8.84.177.00

SUITABLE FOR WORK IN, E.G.:

- Scaffolding
- Construction
- Installation technology
- Aerial platforms
- Offshore
- Petrochemicals

PACKAGING

- 1 piece per polybag
- 2 pieces per case

CE 0598
EN 360:2002

ITEM INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 2 PIECES (CASE)
One size	8.84.177.00	8718249049156	8718249049163

STORAGE REQUIREMENTS

During transport, keep the product in its packaging, well away from any cutting surface; clean it with water, wipe it with a rag and hang it up in a well-ventilated location, to let it dry naturally and away from a naked flame or heat source; follow the same procedure for components that have become damp during use. The system must be stored in its packaging in a dry, well aired place protected from extremes of temperature.

TESTING INSTITUTE

This fall protection is certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link:
www.oxxa-safety.com/doc

RELATED PRODUCTS



FUJI 4015

Harness 3D

Article no. 8.84.015.00



MERU 4176

Fall arrest device
with steel cable 10 m
Article no. 8.84.176.00

YOUR SUPPLIER: